



GENERAL

Place of Build	Fujian South East Shipyard, China
Vessel Type	AHTS
Year Built	2011
Flag	Gibraltar
Call Sign	9V8666
Class	RINA
C - Offshore Support Vesse-Supply Anchor Handling; Fire-Fighting ship - 1 - Unrestricted navigation;Dynapos AM	

PRINCIPAL DIMENSIONS

Length Overall	59.25 metres
Beam	14.95 metres
Maximum Draft	4.95 metres
Net Registered Tonnage	503
Gross Registered Tonnage	1678

MACHINERY & PROPULSION

Main Propulsion Number	2
Main Propulsion Type	CAT 3516B Diesel
Total BHP	5150
Propellers	2 x CPP in Fixed Kort Nozzles
Bow Thruster	1 X Kawasaki KT-72B3 - 515KW 8 TONS
Stern Thruster	1 x Kawasaki KT-55B3 - 390KW 6 TONS
Main Generators	2 x CAT C18 350KW
Shaft Generators	2 x 800KW
Emergency Generators	1 x CAT 65KW
Rudders	Standard

PERFORMANCES

Fuel consumption @ 12 Knots	About 11.5 MT per day
Fuel consumption @ 10 Knots	About 8 MT per day
Fuel consumption @ 8 Knots	About 6 MT per day
Fuel consumption in port	About 0.5 MT per day
Fuel consumption in DP mode	About 6 MT per day

Fuel Type	ISO 8217: 2005 DMA - Marine diesel oil
-----------	--

CARGO CAPABILITIES

Fresh Water	360 m3 @ 100m3 per hr at 75m head
Drill Water	400 m3 @ 100m3 per hr at 75m head
Fuel Capacity (100%)	535 m3 @ 150m3 per hr at 75m head
Liquid Mud	378 m3 @ 70m3 per hr
Dry Bulk	4 X 1650 cu ft each, total 6,600 cu ft
Dead Weight	1360 tons
Clear Deck Area	350 Square Metres
Deck Cargo	500 tons

ACCOMMODATION

Crew	13
Passengers	12
Hospital	yes

COMMUNICATIONS EQUIPMENT

HF radio	FURUNO RC-1500-1T 400W
VHF Radio	2 x FURUNO
Portable VHF Radio's	3 x FURUNO
Satellite Communications (Voice and Fax)	Furuno SAT C
E.P.I.R.B	McMurdo 406
GMDSS Compliance	Area A3

NAVIGATION EQUIPMENT

Radar No. 1	Furuno x-band (21" screen)
Radar No. 2	Furuno x-band (15" screen)
GPS	GP 150
Echo Sounder	Furuno FE 702
Navtex	NX 700
Auto Pilot	Nautopilot NP 60
Gyro Compass	Anchutz STD 22
DP System	Kongsberg

DECK MACHINERY

Tugger Winch	2 x 10 tons @ 15m/min
Capstan	2 x 5 tons @ 15m/min
Deck Crane	1 x 3 tonnes @ 9 m

TOWING & ANCHOR HANDLING

Bollard Pull	65 tons
Winch	Plimsoil Waterfall Type
Line Pull	150 tons
Brake Capacity	200 tons
Anchor Handling Wire and Towing Wire	100m and 1000m x 56mm
Anchor Handling Wire Capacity	100 m x 56 mm
Tow Drum Capacity	1000 m x 56 mm
Spare Tow Wire Capacity	1000 m x 56 mm

Stern Roller	4.0 m x 1.6 m - SWL 200 tonnes
--------------	--------------------------------

Tow Pins	2 x Closed Top Type SWL 200T
Shark Jaws	Shark Jaws - SWL 200T

LIFE SAVING APPARATUS

Liferafts	Total 6, capacity 150 men
Rescue Boat	25 HP OBM, capacity 6 men

EXTERNAL FIRE FIGHTING

Capacity	FIFI 1 - 2400 cu m per hr
Monitor	2 x 1200 cu m per hr
Throw x Height	120 m x 50 m

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented, no guarantees of accuracy can be given. All fuel consumption figures provided without guarantee and subject to actual conditions. For enquires, kindly email us at chartering@it.vroonoffshore.com.